
THIS MANUAL IS DESIGNED TO MAKE IT AS EASY AS POSSIBLE FOR YOU TO SET UP, OPERATE AND MAINTAIN YOUR NEW PORTABLE CRAFT CENTER

Your new Craft Center is a quality piece of equipment that has been carefully designed and manufactured to provide years of dependable service.

Set-up instructions and various usage situations are also provided. Read this manual carefully. Only by being totally aware of what the Craft Center can do will you be able to put it to the numerous tasks it is capable of performing.

CUSTOMER'S RESPONSIBILITIES

The customer is responsible for installing two (2) handle knobs, and four (4) swivel pegs, four (4) corner feet, four (4) screws.




Snap the handles into handle arms on the vise bracket (see inset). Insert swivel grips into holes on vise jaws and you are now ready to use your new Craft Center.

CORNER FOOT ASSEMBLY

LOWER SAWHORSE ASSEMBLY

The Lower Sawhorse feet & screws are shipped in a plastic bag along with the two snap-in handles and 4 swivel pegs.

Assemble the four (4) saw horse feet using the mounting screws provided as shown.



Lower Sawhorse Feet

SAFETY RULES

- 1. Do not load with more than 350 lbs.
- Do not apply an unbalanced load which could cause the Craft Center to tip.
- 3. Do not use Craft Center as a stepladder or standing platform.
- 4. Do not store Craft Center outdoors or in damp condition.
- 5. Be sure that legs lock in the open position.
- Never mount power tools directly in vise; pressure may damage tools.
- 7. An even pressure of jaws on work piece is essential. Tighten both jaw handles uniformly.

GENERAL SAFETY RULES FOR POWER TOOLS USED WITH THE PORTABLE CRAFT CENTER

- 1. KEEP GUARDS IN PLACE and in working order.
- REMOVE ADJUSTING KEYS AND WRENCHES. Form habit of checking to see that keys and adjusting wrenches are removed from tool before turning it on.
- KEEP WORK AREA CLEAN. Cluttered areas and benches invite accidents.
- AVOID DANGEROUS ENVIRONMENT. Don't use power tools in damp or wet locations or expose them to rain. Keep work area well lighted.
- KEEP CHILDREN AWAY, All visitors should be kept a safe distance from work area.
- MAKE WORKSHOP KID-PROOF with padlocks, master switches or by removing starter keys.
- DON'T FORCE TOCL. It will do the job better and safer at the rate for which it was designed.
- 8. USE RIGHT TOOL. Don't force tool or attachment to do a job it was not designed for.
- WEAR PROPER APPAREL. No loose clothing or jewelry to get caught in moving parts. Non-slip footwear is recommended. Wear protective hair covering to contain long hair.
- USE SAFETY GLASSES. Also use face or dust mask if cutting operation is dusty.
- DON'T OVERREACH. Keep proper footing and balance at all times.
- MAINTAIN TOOLS WITH CARE. Keep tools sharp and clean for best and safest performance. Follow instructions for lubricating and changing accessories.
- DISCONNECT TOOLS before servicing; when changing accessories such as blades, bits, cutters, etc.
- 14. CHECK DAMAGED PARTS. Before further use of the tool, a guard or other part that is damaged should be carefully checked to assure that it will operate properly and perform its intended function check for alignment of moving parts, binding of moving parts, breaking of parts, mounting, and any other conditions that may affect its operation. A guard or other part that is damaged should be properly repaired or replaced.
- 15. AVOID UNINTENTIONAL STARTING. Make sure switch is in "Off" position before plugging in.
- 16. GROUND THE OUTLET BOX to prevent possible fatal shocks.
- 17. NEVER LEAVE TOOL RUNNING UNATTENDED.

MAINTENANCE TIPS:

- Pivot screws are of low friction design. No lubrication is necessary.
- If binding of vise jaw occurs, cleaning of pivot nut and vise screw may be required.
- 3. Pivot screws should be checked for tightness.